

# Product data sheet

Specifications



Limit switch body, Limit switches XC Standard, ZCD, compact, 1NC+1 NO, snap action

ZCD21

## Main

|                               |                                                                                                                                                                                                                      |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product              | Telemecanique Limit switches XC Standard                                                                                                                                                                             |
| Series name                   | Standard compact                                                                                                                                                                                                     |
| Product or component type     | Limit switch body                                                                                                                                                                                                    |
| Device short name             | ZCD                                                                                                                                                                                                                  |
| Design                        | Compact                                                                                                                                                                                                              |
| Body type                     | Fixed                                                                                                                                                                                                                |
| Associated head               | ZCE66<br>ZCEH0<br>ZCE08<br>ZCE21<br>ZCE14<br>ZCE13<br>ZCE24<br>ZCE07<br>ZCE02<br>ZCE29<br>ZCE01<br>ZCE63<br>ZCE06<br>ZCE28<br>ZCE27<br>ZCE64<br>ZCE09<br>ZCE65<br>ZCE62<br>ZCE11<br>ZCEH2<br>ZCE10<br>ZCE05<br>ZCE67 |
| Body material                 | Zamak                                                                                                                                                                                                                |
| Number of poles               | 2                                                                                                                                                                                                                    |
| Contacts type and composition | 1 NC + 1 NO                                                                                                                                                                                                          |
| Contact operation             | Snap action                                                                                                                                                                                                          |

## Complementary

|                                 |                                                                  |
|---------------------------------|------------------------------------------------------------------|
| Associated connection component | ZCDEG13<br>ZCDEF12<br>ZCDEN12<br>ZCDEP20<br>ZCDEP16<br>ZCDEG11   |
| Electrical connection           | Screw-clamp terminals, clamping capacity: 1 x 0.34...2 x 1.5 mm² |
| Contacts insulation form        | Zb                                                               |

|                                        |                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Contacts material                      | Silver plated contacts                                                                                                                                                                                                                                                                                                                                              |
| Positive opening                       | With                                                                                                                                                                                                                                                                                                                                                                |
| Minimum actuation speed                | 0.01 m/s                                                                                                                                                                                                                                                                                                                                                            |
| Contact code designation               | B300, AC-15 (Ue = 240 V), Ie = 1.5 A conforming to EN/IEC 60947-5-1 appendix A<br>R300, DC-13 (Ue = 250 V), Ie = 0.1 A conforming to EN/IEC 60947-5-1 appendix A                                                                                                                                                                                                    |
| [Ui] rated insulation voltage          | 300 V conforming to UL 508<br>500 V (pollution degree 3) conforming to IEC 60947-1<br>300 V conforming to CSA C22.2 No 14                                                                                                                                                                                                                                           |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60664<br>6 kV conforming to IEC 60947-1                                                                                                                                                                                                                                                                                                      |
| Short-circuit protection               | 10 A cartridge fuse, type gG                                                                                                                                                                                                                                                                                                                                        |
| Electrical durability                  | 5000000 cycles, DC-13 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Width                                  | 31 mm                                                                                                                                                                                                                                                                                                                                                               |
| Height                                 | 65 mm                                                                                                                                                                                                                                                                                                                                                               |
| Depth                                  | 30 mm                                                                                                                                                                                                                                                                                                                                                               |

## Environment

|                                       |             |
|---------------------------------------|-------------|
| Product compatibility                 | XCKD        |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage   | -40...70 °C |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 4.300 cm  |
| Package 1 Width              | 4.300 cm  |
| Package 1 Length             | 8.100 cm  |
| Package 1 Weight             | 136.000 g |
| Unit Type of Package 2       | S01       |
| Number of Units in Package 2 | 27        |
| Package 2 Height             | 15.000 cm |
| Package 2 Width              | 15.000 cm |
| Package 2 Length             | 40.000 cm |
| Package 2 Weight             | 3.957 kg  |
| Unit Type of Package 3       | P06       |
| Number of Units in Package 3 | 864       |
| Package 3 Height             | 77.000 cm |
| Package 3 Width              | 80.000 cm |
| Package 3 Length             | 60.000 cm |
| Package 3 Weight             | 72.148 kg |

Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                                                                                                             |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                                                                                                                 |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                                                                                                 |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                                                                                                               |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                                                                                                               |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                                                                                                                                     |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Recommended replacement(s)